


## GHAT Balustrade Glazing Channel




### AVAILABLE FINISHES

- Mill finish
- Special colours on request

### TECHNICAL DETAILS

- 6.5m stock length
- Suitable for 12mm glass

## GHAL Balustrade Glazing Channel



## AVAILABLE FINISHES

- Mill finish
- Special colours on request


## TECHNICAL DETAILS

- 6m stock length
- Suitable for 12 and 15mm glass

## GLASS BALUSTRADE PANELS 12mm Standard Panels

## 12mm Standard Panels with Polished Edges &amp; 2mm Polished Radius

CODE	WIDE (mm)	HEIGHT (mm)	AREA (sqm)
BG12-100	100	970	0.10
BG12-150	150	970	0.15
BG12-200	200	970	0.19
BG12-250	250	970	0.24
BG12-300	300	970	0.29
BG12-350	400	970	0.34
BG12-400	400	970	0.38
BG12-450	450	970	0.44
BG12-500	500	970	0.48
BG12-550	550	970	0.53
BG12-600	600	970	0.58
BG12-650	650	970	0.63
BG12-700	700	970	0.67
BG12-750	750	970	0.73
BG12-800	800	970	0.77
BG12-850	850	970	0.82
BG12-900	900	970	0.87
BG12-950	950	970	0.92
BG12-1000	1000	970	0.97
BG12-1050	1050	970	1.01
BG12-1100	1100	970	1.06
BG12-1150	1150	970	1.11
BG12-1200	1200	970	1.16
BG12-1250	1250	970	1.21
BG12-1300	1300	970	1.26
BG12-1350	1350	970	1.3
BG12-1400	1400	970	1.36
BG12-1450	1450	970	1.4
BG12-1500	1500	970	1.45
BG12-1550	1550	970	1.5
BG12-1600	1600	970	1.55
BG12-1650	1650	970	1.6
BG12-1700	1700	970	1.65
BG12-1750	1750	970	1.7
BG12-1800	1800	970	1.75
BG12-1850	1850	970	1.79
BG12-1900	1900	970	1.85
BG12-1950	1950	970	1.89
BG12-2000	2000	970	1.94





## GLASS BALUSTRADE PANELS With 2 Holes

## Balustrade Panels with 2 Holes

CODE	WIDE (mm)	HEIGHT (mm)	AREA (sqm)
BGHG12-600	600	970	0.58
BGHG12-650	650	970	0.63
BGHG12-700	700	970	0.68
BGHG12-750	750	970	0.73
BGHG12-800	800	970	0.78
BGHG12-850	850	970	0.82
BGHG12-900	900	970	0.87
BGHG12-950	950	970	0.92
BGHG12-1000	1000	970	0.97
BGHG12-1050	1050	970	1.02
BGHG12-1100	1100	970	1.07
BGHG12-1150	1150	970	1.12
BGHG12-1200	1200	970	1.16
BGHG12-1250	1250	970	1.21
BGHG12-1300	1300	970	1.26
BGHG12-1350	1350	970	1.31
BGHG12-1400	1400	970	1.36
BGHG12-1450	1450	970	1.41
BGHG12-1500	1500	970	1.46
BGHG12-1550	1550	970	1.5
BGHG12-1600	1600	970	1.55
BGHG12-1650	1650	970	1.6
BGHG12-1700	1700	970	1.65
BGHG12-1750	1750	970	1.7
BGHG12-1800	1800	970	1.75

## Balustrade Glass with Holes for Handrail





## GLASS BALUSTRADE PANELS 4 / 6 Holes

## Balustrade Panels with 4/6 Holes

CODE	WIDE (mm)	HEIGHT (mm)	AREA (sqm)	HOLES
BGHG12-600	600	1280	0.77	4 Holes
BGHG12-650	650	1280	0.83	4 Holes
BGHG12-700	700	1280	0.90	4 Holes
BGHG12-750	750	1280	0.96	4 Holes
BGHG12-800	800	1280	1.02	4 Holes
BGHG12-850	850	1280	1.09	4 Holes
BGHG12-900	900	1280	1.15	4 Holes
BGHG12-950	950	1280	1.22	4 Holes
BGHG12-1000	1000	1280	1.28	4 Holes
BGHG12-1050	1050	1280	1.34	4 Holes
BGHG12-1100	1100	1280	1.41	4 Holes
BGHG12-1150	1150	1280	1.47	4 Holes
BGHG12-1200	1200	1280	1.54	4 Holes
BGHG12-1250	1250	1280	1.60	4 Holes
BGHG12-1300	1300	1280	1.66	4 Holes
BGHG12-1350	1350	1280	1.73	4 Holes
BGHG12-1400	1400	1280	1.79	4 Holes
BGHG12-1450	1450	1280	1.86	4 Holes
BGHG12-1500	1500	1280	1.92	6 Holes
BGHG12-1550	1550	1280	1.98	6 Holes
BGHG12-1600	1600	1280	2.05	6 Holes
BGHG12-1650	1650	1280	2.11	6 Holes
BGHG12-1700	1700	1280	2.18	6 Holes
BGHG12-1750	1750	1280	2.24	6 Holes
BGHG12-1800	1800	1280	2.30	6 Holes

## 12MM TOUGHENED GLASS Side Fixing Standard Size Panel



## AVAILABLE FINISHES

- 12mm Clear Toughened Glass

## TECHNICAL DETAILS

- Side fixing standard size panel

## POSIGLAZE Glass Balustrade System



### DESCRIPTION

The PosiGlaze Glass Balustrade System was developed for cantilevered structural balustrades to cope with the transition from monolithic toughened safety glass to toughened laminated safety glass.

The unique design uses a special high strength hollow core aluminium extrusion and special glass clamp kits that clamp the glass and locate into the section. This means the system can be used on 12, 15, & 19mm toughened safety glass and 13.5, 17.5 and 21.5 laminated safety glass without holes in the glass. Holes can make the systems more complex and often the holes are the point of failure.

The other key to PosiGlaze is its clever locating and adjusting technique which allows the installers to adjust the glass panels once in place, with a turn of a spanner, saving on installation time.

### SUITABLE FOR

The PosiGlaze Glass Balustrade System can be base fixed or side fixed for top or side (face) mounted balustrade applications.

The 120mm high x 72mm wide extrusion comes in 3 meter lengths all pre drilled ready for fixing and once the section is fitted the glass is easily dropped in and located. The systems also make re-glazing easy, or the glass type or thickness can be easily changed to a later date.

A top seal strip section and gasket are installed after the glass has been adjusted to give a clean top edge look and matching end caps complete the system.

For the side fixed systems an additional clip on side cladding and tapered base cladding section is used for aesthetics and to cover the fixing holes.

### AVAILABLE FINISHES

The sections and cover are fully anodized for durability and come standard in a unique brushed anodized finish which give a "Stainless Steel Effect".

Other aluminium finishes are available on request.

## PG120.B / PG120.S / PG180.S PosiGlaze Balustrade System

**DESIGN AND TESTING**

The PosiGlaze Glass Balustrade System has been designed and tested to New Zealand and British Standards, which use similar occupancy types and loading requirements.

The UK testing BS 6180:2011, involved base and side fixed systems to concrete and steel a range of glass types and thicknesses from 15mm - 21mm including TLSG with EVA and SG inter layer.

The NZ testing is to AS/NZS 1170 loadings in accordance with B1/VM1 Amend 8, for Occupancy A, B, E, C3 and the higher C1, C2 and D loadings.

Therefore the systems can be used for all residential applications, except for C5 (over-crowding).

**INSTALLATION**

The PosiGlaze Glass Balustrade System can be glazed with Toughened, Heat Soaked, screen printed, Digital printed, Toughened Safety Glass (TSG) or SafeLite Toughened Laminated Safety Glass (TLSG), using either PVB, CIP, EVA or SGP interlayer. Note that the breakage characteristic can alter with different interlayer's.

(Refer to Glass Manufacturer for more details)

**COMPLIANCE**

The PosiGlaze Glass Balustrade System can be used for compliance with NZ Building Code Clause F4-Safety from falling, with barrier heights to suit the design application, normally 1 metre.


The maximum glass height is a function of the glass type, thickness, occupancy loading, and wind loading and a design table or specific design is available.

Test data and independent engineered and certified Producer Statements (PS1) are available for compliance with the NZ building code.


Heat soaked TSG is recommended for barriers with interlinking handrails or top rails.

**PG120.B**


- Base fix system
- 120mm x 72mm x 3m

**PG120.S**

- Side fix system
- 120mm x 74mm x 3m

**PG180.S**

- Side fix system
- 180mm x 74mm x 3m





## BA124 Infinity Sidefix Glass Balustrade System

### DESCRIPTION

- Infinity sidefix glass balustrade system.
- No holes are required in the glass panels, they are simple to install, align and adjust.
- Residential A, C3 and pool fencing require 12mm toughened glass, clamps at 500mm centres with a maximum overhang of 250mm.
- Commercial B,E and C3 require 15mm toughened glass, clamps at 400mm centres with a maximum overhang of 200mm.
- PS1 and system manual with full set out details are available on request

### SUITABLE FOR





- Side fix frameless glass balustrades.
- Pool fencing and the following balustrade occupancy types - Residential A and CS, Commercial B, E and C3.

### AVAILABLE FINISHES

- Natural anodised aluminium with mill finish.
- Standard colour powder coat options also available.

### ORDER


- Specify lengths of front and rear covers, plus the required number of glass clamps. All system components can be selected on pages to follow.



## BA124 Infinity Sidefix Glass Balustrade System

### TIMBER DECK - M12 COACH SCREW


- Occupancy
- Residential and C3 only



1. Coachscrews 90mm minimum thread engagement into joists.
2. Bond all coachscrews with SIKa Supergrip to full depth.
3. A rubber, EPDM or foam tape layer must be installed between the clamp and timber.


### WATERPROOF TIMBER DECK - M12 COACH SCREW

- Occupancy
- Residential and C3 only




1. Coachscrews 90mm minimum thread engagement into joists.
2. Bond all coachscrews with SIKa Supergrip to full depth.
3. A rubber, EPDM or foam tape layer must be installed between the clamp and timber.


### INFINITY GLASS CLAMPS HEIGHT OPTIONS




'Normal' height say 10mm below deck



Clamp flush with deck



Clamp below deck




Clamp flush with deck 15mm spacer

## BA124 Infinity Sidefix Glass Balustrade System

### CONCRETE DECK - M12 STUD


- Occupancy
- Residential A & C3 = 12mm toughened glass
- Residential B, E & C3 = 15mm toughened glass



1. All fixings must engage into the structural slab.
2. A rubber, EDPM or foam type layer must be installed between the clamp and concrete.


### STEEL STRUCTURE - M12 BOLT

- Occupancy
- Residential A and C3 = 12mm glass
- Commercial B, E or C3 = 15mm glass




1. A rubber, EDPM or foam type layer must be installed between the clamp and steel.


### INFINITY GLASS CLAMPS HEIGHT OPTIONS




'Normal'  
height say  
10mm  
below deck



Clamp  
flush  
with deck



Clamp  
below  
deck




Clamp flush  
with deck  
15mm spacer

## BA124 Infinity Sidefix Glass Balustrade System

### WATERPROOF TIMBER DECK


- Occupancy
- Commercial B, E or C3



1. Coachscrews 120mm minimum thread engagement into joists.
2. Bond all coachscrews with SIKa Supergrip to full depth.
3. A rubber, EPDM or foam tape layer must be installed between the clamp and timber.


### TIMBER DECK - M12 COACH SCREW

- Occupancy
- Commercial B, E or C3




1. Coachscrews 90mm minimum thread engagement into joists.
2. Bond all coachscrews with SIKa Supergrip to full depth.
3. A rubber, EPDM or foam tape layer must be installed between the clamp and timber.


### INFINITY GLASS CLAMPS HEIGHT OPTIONS




'Normal' height say 10mm below deck



Clamp flush with deck



Clamp below deck



Clamp flush with deck 15mm spacer



## CKI.1 Infinity Heavy Duty Clamp Extrusion

### TECHNICAL DETAILS



- Infinity heavy duty clamp extrusion.
- The infinity balustrade clamp comes as a kit - clamp extrusion, front and rear gasket extrusions gaskets, glass bottom packer and all adjusting screws (M12 fastner not included).

### SUITABLE FOR

- 12mm, 13.52mm, 15mm, 17.52mm, 19mm and 21.52mm glass thickness.

### AVAILABLE FINISHES

- Aluminium



**RC1 SERIES** Rear Cover / Clamp Base with Bulb Seal (template)**RCI SERIES ITEM NUMBERS**


- RC1.118.N.5000 - 118mm height, natural anodised, 5m
- RC1.118.N.2500 - 118mm height, natural anodised, 2.5m
- RC1.118.M.5000, 118mm height, mill aluminium, 5m
- RC1.118.M.2500, 118mm height, mill aluminium, 2.5m

**SUITABLE FOR**

- Infinity system

**AVAILABLE FINISHES**

- Natural anodised
- Mill aluminium
- Standard dulux colours (same price as natural anodised if 25lm or more, if less than 25lm then P.O.A.)

**FCI SERIES** Front Cover with Bulb Seal**RCI SERIES ITEM NUMBERS**


- FC1.124.N.5000, 124mm height, natural anodised, 5m
- FC1.124.N.2500, 124mm height, natural anodised, 2.5m
- FC1.124.M.5000, 124mm height, mill aluminium, 5m
- FC1.124.M.2500, 124mm height, mill aluminium, 2.5m

**SUITABLE FOR**

- Infinity system

**AVAILABLE FINISHES**

- Natural anodised
- Mill aluminium
- Standard dulux colours (same price as natural anodised if 25lm or more, if less than 25lm then P.O.A.)




## CKI.12 Clamp Kit - 12mm glass

### TECHNICAL DETAILS

- Infinity system
- 12mm glass thickness

### AVAILABLE FINISHES

- Natural anodised
- Mill




## CKI.15 Clamp Kit - 15mm glass

### TECHNICAL DETAILS

- Infinity system
- 15mm glass thickness

### AVAILABLE FINISHES

- Natural anodised
- Mill




## RSI.1 Rear Cover Spacer Plate

## TECHNICAL DETAILS

- 1mm to align rear cover if structure is not straight
- Use only if required

## AVAILABLE FINISHES

- Silver frost
- Mill




## SOI.15 Stand Off Plate

## TECHNICAL DETAILS

- Will stand the infinity system 15mm off the structure
- Use only if required

## AVAILABLE FINISHES

- Silver frost
- Mill






**EC.124.6 / EC.124.7 Extrusion End Cap****TECHNICAL DETAILS**


- EC1.124.6, no.6 plastic plug + 6g x 25 SS CS screw
- EC1.124.7, no.7 plastic plug + z x 25 SS CS screw

**AVAILABLE FINISHES**

- Natural anodised
- Mill

**GGSI.F / GGSI.R Glass Gasket Set Front and Rear****TECHNICAL DETAILS**

- GGSI.F - front
- GGSI.R - rear





**GGL.12F / GGL.12R Glass Gasket For 12/15mm Glass Thickness****TECHNICAL DETAILS**

- GGL.12F (front for 12mm thick glass) - 2mm thick x 100mm wide
- GGL.12R (rear for 12mm thick glass) - 2mm thick x 150mm wide
- GGL.15F (front for 15mm thick glass) - 1mm thick x 100mm wide
- GGL.14R (rear for 15mm thick glass) - 1mm thick x 150mm wide

**AVAILABLE FINISHES**

- Natural anodised
- Mill

**GBS.124 Glass Bulb Seal**



riba  
product  
selector

**TESTED**  
according to  
**BS6180**

Model 6020 | 6021

## 1.5KN TOP AND SIDE MOUNT

- | Quick and simple mounting
- | Different finishes
- | For glass thicknesses between 12 - 21,52 mm
- | Drainage holes
- | Increased stability with the same looks
- | For applications requiring 0.74Kn the mounting distance can be 600mm
- | Private, commercial and public areas

WE'RE ONLEVEL | [WWW.ONLEVEL.COM](http://WWW.ONLEVEL.COM)

# TL-6020

1.5 kN Top Mount

## Level Up.

The Profile TL-6020 is the intelligent onward development of the TL-6010 Profile. Here the outstanding feature consists in the increase of mounting distances, which now enables the use of the profile also on an anchor bolt without countersunk head. Therefore, mounting the product is not only faster and more cost efficient, but also statics have improved considerably.

It can be used in exterior applications, withstands a linear load of 1.5 kN and is appropriate for glass thicknesses between 12 mm and 21.52 mm.

## Essential Features





- | Slimline, elegant design and low-maintenance
- | **ONLEVEL** Flex-Fit Glass Adjustment Tool
- | Extension pin holes
- | Drainage holes
- | For use with Top Cover 3.0 kN
- | For glass thicknesses between 12 - 21.52 mm
- | For applications of 0.74kN in private areas, the mounting distance amounts to 60 cm



**CAD** IN EVERY FORMAT



**TESTED**  
according to  
**BS6180**





Increased stability with the same looks

Integrated multifunctional sophisticated chamber for enabling larger drilling distances



Top mount



# TL-6020 | 1.5 KN TOP MOUNT

## Glass profile




| Height: 140 mm  
| Width: 60 mm  
| Sales unit: 1 piece

Model 6020	Mill finish	Plain aluminium	Stainless steel look	Coloured
Length	Art. no.	Art. no.	Art. no.	Art. no.
2500	-	10.6020.002.11	10.6020.002.12	-
5000	10.6020.005.10	10.6020.005.11	10.6020.005.12	10.6020.005.13/16

## Inside corner / outside corner 90°



| Side length inside 140 mm  
| Side length outside 200 mm  
| Sales unit: 1 piece



Model 6020	Mill finish	Plain aluminium	Stainless steel look	Coloured
	Art. no.	Art. no.	Art. no.	Art. no.
	10.6020.390.10	10.6020.390.11	10.6020.390.12	10.6020.390.13/16

## End cap, left/right



| For use on the left and right  
| Sales unit: 1 piece

Model 6020	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
left/right	10.6020.490.10	10.6020.490.11	10.6020.490.12	10.6020.490.13/16

## Spacer

You do not have any drainage options on your balcony?!  
So that you do not need to install a dam on your balcony, you can simply mount the spacers beneath your profile.



| Inner drill hole Ø 14 mm  
| Sales unit: 13 pieces

Model 6020	Mill finish	Plain aluminium	Stainless steel look	Coloured
	Art. no.	Art. no.	Art. no.	Art. no.
	10.6020.500.10	10.6020.500.11	10.6020.500.12	10.6020.500.13/16

# TL-6020 | 1.5 KN TOP MOUNT

## Extension pin



- | Length 40 mm
- | Diameter Ø 6 mm
- | Sales unit: 8 piece



Model 7001	V4A (interior & exterior)
Art. no.	
90.7001.640.31	

## Fischer fixing anchor FIS AM M10x150



- | Finish interior application: zinc-plated steel (interior)
- | Finish exterior application: V4A (exterior)
- | Required number per 2500 mm: 13 pieces
- | Sales unit: 25 pieces



Model 3511	Zinc-plated steel (interior)	V4A (exterior)
Art. no.		Art. no.
91.3551.015.81		91.3551.015.30

## Fixing anchor steel

- | Finish interior application: zinc-plated steel (interior)
- | Finish exterior application: V4A (exterior)
- | Required number per 2500 mm: 13 pieces
- | Sales unit: 13 pieces



Model 6020	Zinc-plated steel (interior)	V4A (exterior)
Art. no.		Art. no.
91.6020.060.81		91.6020.060.30

# TL-6020 | 1.5 KN TOP MOUNT

## Flex-Fit 1.0 kN




- | Fine adjustment of glass panes
- | For glass thicknesses between 12 - 21.52 mm
- | Adjustment of up to 34 mm in relation to the vertical axis
- | Pay attention to the right glass thickness!

Length		2500 mm	5000 mm	25 mtr
Glass thickness	Wedge colour	Art. no.	Art. no.	Art. no.
12 mm	black	90.0502.112.00	90.0505.112.00	90.0525.112.00
6/6/2 (12.76 mm)	red	90.0502.113.00	90.0505.113.00	90.0525.113.00
6/6/4 (13.52 mm)	grey	90.0502.114.00	90.0505.114.00	90.0525.114.00
15 mm	yellow	90.0502.115.00	90.0505.115.00	90.0525.115.00
<b>8/8/2 (16.76 mm)</b>	brown	90.0502.117.00	90.0505.117.00	90.0525.117.00
<b>8/8/4 (17.52 mm)</b>	green	90.0502.118.00	90.0505.118.00	90.0525.118.00
19 mm	blue	90.0502.119.00	90.0505.119.00	90.0525.119.00
<b>10/10/2 (20.76 mm)</b>	red	90.0502.121.00	90.0505.121.00	90.0525.121.00
<b>10/10/4 (21.52 mm)</b>	green	90.0502.122.00	90.0505.122.00	90.0525.122.00



# MOUNTING INSTRUCTION FLEXFIT



# TL-6021

1.5 kN Side Mount





## The Evolution Goes On.

The Profile TL-6021 is the intelligent onward development of the TL-6011 Profile. Here the outstanding feature consists in the increase of mounting distances, which now enables the use of the profile also on an anchor bolt without countersunk head. This makes mounting the product not only much quicker and more cost efficient, also statics have improved significantly.

The Profile TL-6021 can be used for exterior applications. It can withstand a linear load of 1.5 kN and is appropriate for glass thicknesses between 12 mm and 21.52 mm.

## Essential Features

- | Slimline, elegant design and low-maintenance
- | **ONLEVEL** Flex-Fit Glass Adjustment Tool
- | Drainage holes
- | Cover (optional)
- | For use with Top Cover 3.0 kN
- | For glass thicknesses between 12 mm and 21.52 mm
- | For applications of 0.74kN in private areas, the mounting distance amounts to 40 cm





Improved statics

Can be anchored universally  
depending on the application



Side mount

Integrated multifunctional  
sophisticated chamber for  
enabling larger drilling  
distances

# TL-6021 | 1.5 KN SIDE MOUNT

## Glass profile



| Height: 140 mm  
| Width: 60 mm  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Length	Art. no.	Art. no.	Art. no.	Art. no.
2500	-	10.6021.002.11	10.6021.002.12	-
5000	10.6021.005.10	10.6021.005.11	10.6021.005.12	10.6021.005.13/16

## Inside corner 90°



| Side length inside 140 mm  
| Side length outside 200 mm  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
	Art. no.	Art. no.	Art. no.	Art. no.
	10.6021.300.10	10.6021.300.11	10.6021.300.12	10.6021.300.13/16

## Outside corner 90°



| Side length inside 140 mm  
| Side length outside 200 mm  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
	Art. no.	Art. no.	Art. no.	Art. no.
	10.6021.350.10	10.6021.350.11	10.6021.350.12	10.6021.350.13/16

## End cap, left



| For use on the left  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
left	10.6021.400.10	10.6021.400.11	10.6021.400.12	10.6021.400.13/16

# TL-6021 | 1.5 KN SIDE MOUNT

## End cap, left, with cover cap



| For use on the left  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
left	10.6021.410.10	10.6021.410.11	10.6021.410.12	10.6021.410.13/16

## End cap, right



| For use on the right  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
right	10.6021.450.10	10.6021.450.11	10.6021.450.12	10.6021.450.13/16

## End cap, right, with cover cap



| For use on the right  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
right	10.6021.460.10	10.6021.460.11	10.6021.460.12	10.6021.460.13/16

## End cap for staircase with cover strip, left



| For use on the left  
| can be cut to size  
| Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
left	10.6021.411.10	10.6021.411.11	10.6021.411.12	10.6021.411.13/16

# TL-6021 | 1.5 KN SIDE MOUNT

## End cap for staircase with cover strip, right



- | For use on the right
- | can be cut to size
- | Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Application	Art. no.	Art. no.	Art. no.	Art. no.
right	10.6021.461.10	10.6021.461.11	10.6021.461.12	10.6021.461.13/16

## Cover strip



- | With mounting strips
- | For use with a cover cap, end caps must be ordered separately.
- | Sales unit: 1 piece

Model 6021	Mill finish	Plain aluminium	Stainless steel look	Coloured
Length	Art. no.	Art. no.	Art. no.	Art. no.
2500	-	10.6021.202.11	-	-
5000	10.6021.205.10	10.6021.205.11	10.6021.205.12	10.6021.205.13/16

## Blanking plug



- | Required number per 2500 mm: 17 pieces
- | Sales unit: 10 pieces

Model 7000		Plastic
Colour	Diameter	Art. no.
white	30 mm	90.7000.030.40
black	30 mm	90.7000.030.41
grey	30 mm	90.7000.030.45

## Extension pin



- | Length 40 mm
- | Diameter Ø 6 mm
- | Sales unit: 8 piece

Model 7001	V4A (interior & exterior)
	Art. no.
	90.7001.640.31

# TL-6021 | 1.5 KN SIDE MOUNT

## Fischer fixing anchor FH II 12/10



- | Finish interior application: zinc-plated steel (interior)
- | Finish exterior application: V4A (exterior)
- | Required number per 2500 mm: 13 pieces
- | Sales unit: 50 pieces

Model 3521	Zinc-plated steel (interior)	V4A (exterior)
	Art. no.	Art. no.
	91.3521.210.81	91.3521.210.30

## Fixing anchor steel



- | Finish interior application: zinc-plated steel (interior)
- | Finish exterior application: V4A (exterior)
- | Required number per 2500 mm: 13 pieces
- | Sales unit: 13 pieces

Model 6021	Zinc-plated steel (interior)	V4A (exterior)
	Art. no.	Art. no.
	91.6021.060.81	91.6021.060.30

## Befestigungsanker Rampa Holz



- | Finish interior application: zinc-plated steel (interior)
- | Required number per 2500 mm: 13 pieces
- | Sales unit: 13 pieces

Modell 3011	Zinc-plated steel (interior)
	Art. no.
	91.6021.800.81




# TL-6021 | 1.5 KN SIDE MOUNT

## Flex-Fit 1.0 kN



- | Fine adjustment of glass panes
- | For glass thicknesses between 12 - 21.52 mm
- | Adjustment of up to 34 mm in relation to the vertical axis
- | Pay attention to the right glass thickness!

Length		2500 mm	5000 mm	25 mtr
Glass thickness	Wedge colour	Art. no.	Art. no.	Art. no.
12 mm	black	90.0502.112.00	90.0505.112.00	90.0525.112.00
6/6/2 (12.76 mm)	red	90.0502.113.00	90.0505.113.00	90.0525.113.00
6/6/4 (13.52 mm)	grey	90.0502.114.00	90.0505.114.00	90.0525.114.00
15 mm	yellow	90.0502.115.00	90.0505.115.00	90.0525.115.00
<b>8/8/2 (16.76 mm)</b>	brown	90.0502.117.00	90.0505.117.00	90.0525.117.00
<b>8/8/4 (17.52 mm)</b>	green	90.0502.118.00	90.0505.118.00	90.0525.118.00
19 mm	blue	90.0502.119.00	90.0505.119.00	90.0525.119.00
<b>10/10/2 (20.76 mm)</b>	red	90.0502.121.00	90.0505.121.00	90.0525.121.00
<b>10/10/4 (21.52 mm)</b>	green	90.0502.122.00	90.0505.122.00	90.0525.122.00



Spacer





# DRAINAGE – BUT NOT A RAIN GUTTER.

If water and cold combine, this can lead to problems when using all-glass balustrades. For this purpose, all **ONLEVEL** glass support profiles are equipped with drainage holes with a distance of 1000 mm between each of them. And we wouldn't be **ONLEVEL**, if we hadn't thought of all sorts of situations. Depending on the season, the balustrade can be subject to the most different influences (e.g.: leaves, sand, dirt).

**We offer the only profile of this kind on the market.**

**ONLEVEL** has paid special attention to ensure that the pivot point of the glass is on the same level as the rubber seals – therefore the rubber seals are never directly subjected to an increased or decreased load. As a result, dirt affects the balustrade much less.





**GHA Solutions**

Unit E8  
53-75 Queens Road  
Five Dock NSW 2046  
(Entrance off William Street Dock 5)

Mobile: 0410 313 780  
Fax: 02 97010410